

appending means for appending said copy management information to said compressed video data; and

recording means for recording said compressed video data with appended copy management information, said copy management information being recorded at a pre-set position of a record medium.

60(new). The recorder according to claim 59, wherein said copy protection signal is a signal coded with plural bits, is located at a pre-set position of said analog video signal and is indicative of a copy generation limitation.

61(new). The recorder according to claim 60, wherein said pre-set position of said analog video signal is a pre-set horizontal period within a vertical blanking period of said analog video signal.

62(new). The recorder according to claim 61, wherein said pre-set horizontal period is the twentieth horizontal period within said vertical blanking period.

63(new). The recorder according to claim 59, wherein said pre-set position of said record medium is located within a data area and/or a lead-in area of said record medium.

64(new). The recorder according to claim 63, wherein said pre-set position of said record medium is located within a header portion which is within said data area of said record medium.

09085733-062001  
a2

65(new). The recorder according to claim 59, wherein said digital video data is partitioned into units and said copy management information is located in at least one of said units.

66(new). The recorder according to claim 59, wherein said record medium is an optical disc, a magneto-optical disc, a magnetic hard disk or an integrated circuit (IC) memory card.

67(new). The recorder according to claim 59, wherein said analog video signal is an analog video signal having a combination signal of plural pseudo synchronization pulses and plural white peak signals across plural horizontal periods in a vertical blanking period of said analog video signal.

68(new). The recorder according to claim 59, wherein said analog video signal is an analog color video signal having an associated color burst signal and wherein the phase of at least a portion of said color burst signal is changed from an original state.

69(new). The recorder according to claim 68, wherein said copy protection signal is a signal coded with plural bits, is located at a pre-set position of said analog video signal and is indicative of a limitation on recording.

70(new). A digital video signal recorder capable of inhibiting unauthorized copying of an analog video signal, comprising:

an input terminal for receiving said analog video signal, said analog video signal including a copy protection signal;

09885733-062001

Q2

analog-to-digital converting means for converting said analog video signal to digital video data;

compression means for compressing said digital video data to generate compressed video data;

detecting means for detecting said copy protection signal included in said analog video signal;

generating means for generating copy management information according to a state of said copy protection signal detected by said detecting means;

scrambling means for generating scrambled video data by scrambling said compressed video data according to key information; and

recording means for recording said scrambled video data with said key information, said key information being recorded at a pre-set position of a record medium.

71(new). The recorder according to claim 70, wherein said pre-set position of said record medium is located within a data area and/or a lead-in area of said record medium.

72(new). The recorder according to claim 71, wherein said pre-set position of said record medium is located within a header portion which is within said data area of said record medium.

73(new). The recorder according to claim 72, wherein said digital video data is partitioned into units and said key information is located in at least one of said units.

09885733-062001  
000290-EE/58860  
a2

74(new). The recorder according to claim 70, wherein said key information corresponds to bit sequence data used to implement the scrambling.

75(new). A digital video signal recorder capable of inhibiting unauthorized copying of an analog video signal, comprising:

an input terminal for receiving said analog video signal, said analog video signal including a copy protection signal;

analog-to-digital converting means for converting said analog video signal to digital video data;

compression means for compressing said digital video data to generate compressed video data;

detecting means for detecting said copy protection signal included in said analog video signal;

generating means for generating copy management information according to a state of said copy protection signal detected by said detecting means;

scrambling means for generating scrambled video data by scrambling said compressed video data according to key information;

appending means for appending said copy management information to said scrambled video data; and

recording means for recording said scrambled video data with said copy management information and said key information, said copy management information and said key information being recorded at a pre-set position of a record medium.

09885733-062001

76(new). The recorder according to claim 75, wherein said copy protection signal is a signal coded with plural bits, is located at a pre-set position of said analog video signal and is indicative of a copy generation limitation.

77(new). The recorder according to claim 75, wherein said pre-set position of said record medium is located within a data area and/or a lead-in area of said record medium.

78(new). The recorder according to claim 77, wherein said pre-set position of said record medium is located within a header portion which is within said data area of said record medium.

79(new). The recorder according to claim 75, wherein said key information corresponds to bit sequence data used to implement the scrambling.

80(new). A digital video signal recording method through which unauthorized copying of an analog video signal can be inhibited, comprising the steps of:

receiving said analog video signal, said analog video signal including a copy protection signal;

performing an analog-to-digital conversion on said analog video signal to generate digital video data;

compressing said digital video data to generate compressed video data;

detecting said copy protection signal included in said analog video signal;

generating copy management information according to a state of said copy protection signal detected in said step of detecting;

09885733-062004  
100290-0058860

appending said copy management information to said compressed video data; and  
recording said compressed video data with appended copy management  
information, said copy management information being recorded at a pre-set position of a record  
medium.

81(new). The recording method according to claim 80, wherein said copy protection signal is a  
signal coded with plural bits, is located at a pre-set position of said analog video signal and is  
indicative of a copy generation limitation.

82(new). The recording method according to claim 80, wherein said pre-set position of said  
analog video signal is a pre-set horizontal period within a vertical blanking period of said analog  
video signal.

83(new). The recording method according to claim 82, wherein said pre-set horizontal period is  
the twentieth horizontal period within said vertical blanking period.

84(new). The recording method according to claim 80, wherein said pre-set position of said  
record medium is located within a data area and/or a lead-in area of said record medium.

85(new). The recording method according to claim 84, wherein said pre-set position of said  
record medium is located within a header portion which is within said data area of said record  
medium.

09885733-062001

86(new). The recording method according to claim 80, wherein said digital video data is partitioned into units and said copy management information is located in at least one of said units.

87(new). The recording method according to claim 80, wherein said record medium is an optical disc, a magneto-optical disc, a magnetic hard disk or an integrated circuit (IC) memory card.

88(new). The recording method according to claim 80, wherein said analog video signal is an analog video signal having a combination signal of plural pseudo synchronization pulses and plural white peak signals across plural horizontal periods in a vertical blanking period of said analog video signal.

89(new). The recording method according to claim 80, wherein said analog video signal is an analog color video signal having an associated color burst signal and wherein the phase of at least a portion of said color burst signal is changed from an original state.

90(new). The recording method according to claim 89, wherein said copy protection signal is a signal coded with plural bits, is located at a pre-set position of said analog video signal and is indicative of a limitation on recording.

91(new). A digital video signal recording method through which unauthorized copying of an analog video signal can be inhibited, comprising the steps of:

Q2  
09885733-062001

receiving said analog video signal, said analog video signal including a copy protection signal;

performing an analog-to-digital conversion on said analog video signal to generate digital video data;

compressing said digital video data to generate compressed video data;

detecting said copy protection signal included in said analog video signal;

generating copy management information according to a state of said copy protection signal detected in said step of detecting;

scrambling said compressed video data according to key information to generate scrambled video data; and

recording said scrambled video data with said key information, said key information being recorded at a pre-set position of a record medium.

92(new). The recording method according to claim 91, wherein said pre-set position of said record medium is located within a data area and/or a lead-in area of said record medium.

93(new). The recording method according to claim 92, wherein said pre-set position of said record medium is located within a header portion which is within said data area of said record medium.

94(new). The recording method according to claim 93, wherein said digital video data is partitioned into units and said key information is located in at least one of said units.

az  
09885733-062001



95(new). The recording method according to claim 91, wherein said key information corresponds to bit sequence data used to implement the scrambling.

96(new). A digital video signal recording method through which unauthorized copying of an analog video signal can be inhibited, comprising the steps of:

receiving said analog video signal, said analog video signal including a copy protection signal;

performing an analog-to-digital conversion on said analog video signal to generate digital video data;

compressing said digital video data to generate compressed video data;

detecting said copy protection signal included in said analog video signal;

generating copy management information according to a state of said copy protection signal detected in said step of detecting;

scrambling said compressed video data according to key information to generate scrambled video data;

appending said copy management information to said scrambled video data; and

recording said scrambled video data with said copy management information and said key information, said copy management information and said key information being recorded at a pre-set position of a record medium.

97(new). The recording method according to claim 96, wherein said copy protection signal is a signal coded with plural bits, is located at a pre-set position of said analog video signal and is indicative of a copy generation limitation.

09085733-062001  
A2

98(new). The recording method according to claim 96, wherein said pre-set position of said record medium is located within a data area and/or a lead-in area of said record medium.

99(new). The recording method according to claim 96, wherein said pre-set position of said record medium is located within a header portion which is within said data area of said record medium.

100(new). The recording method according to claim 98, wherein said key information corresponds to bit sequence data used to implement the scrambling.

101(new). A digital video signal recorder capable of inhibiting unauthorized copying of an analog video signal, comprising:

an input terminal for receiving said analog video signal, said analog video signal including a copy protection signal;

analog-to-digital converting means for converting said analog video signal to digital video data;

compression means for compressing said digital video data to generate compressed video data;

detecting means for detecting said copy protection signal included in said analog video signal;

generating means for generating copy management information according to a state of said copy protection signal detected by said detecting means;

09885733-062001

scrambling means for generating scrambled video data by scrambling said compressed video data according to said copy management information; and  
encoding and modulating means for recording said scrambled video data and said copy management information on a record medium, said copy management information being recorded at a pre-set position of said record medium.

102(new). The recorder according to claim 101, wherein said pre-set position of said record medium is located within a header portion of a data area and/or a lead-in area of said record medium.

103(new). A digital signal recorder capable of inhibiting unauthorized copying of an analog signal, comprising:

an input terminal for receiving said analog signal, said analog signal including a copy protection signal;

analog-to-digital converting means for converting said analog signal to digital data;

compression means for compressing said digital data to generate compressed data;

detecting means for detecting said copy protection signal included in said analog signal, said copy protection signal being a signal coded with plural bits, being located at a pre-set position of said analog signal and being indicative of a copy generation limitation;

generating means for generating copy management information according to a state of said copy protection signal detected by said detecting means;

appending means for appending said copy management information to said compressed data; and

recording means for recording said compressed data with appended copy management information, said copy management information being recorded at a pre-set position of a record medium.

104(new). A digital signal recorder capable of inhibiting unauthorized copying of an analog signal, comprising:

an input terminal for receiving said analog signal, said analog signal including a copy protection signal;

analog-to-digital converting means for converting said analog signal to digital data;

compression means for compressing said digital data to generate compressed data;

detecting means for detecting said copy protection signal included in said analog signal, said copy protection signal being a signal coded with plural bits, being located at a pre-set position of said analog signal and being indicative of a copy generation limitation;

generating means for generating copy management information according to a state of said copy protection signal detected by said detecting means;

scrambling means for generating scrambled data by scrambling said compressed data according to said copy management information; and

encoding and modulating means for recording said scrambled data and said copy management information on a record medium.

09885733-062001  
T002290-EE758860